



LA11075

Artemide Architectural Vector Magnetic LED Track Light

SOURCE: <https://www.davidvillagelighting.co.uk/product/Artemide-Architectural-Vector-Magnetic-LED-Track-Light/10001992>

PRODUCT DESCRIPTION

Designer: Carlotta de Bevilacqua

Artemide Architectural Vector Magnetic LED Track Light



The Artemide Architectural Vector Magnetic LED Track Light has been developed for use with the A.24 magnetic track system, offering a compact, directional spotlight that can be repositioned easily along the profile. Each head is fitted with a junction arm that integrates the magnetic coupling and keeps the centre of gravity aligned with the track, helping to maintain a clean, ordered appearance even when the spotlight is tilted or rotated. Once in place, the Vector head can rotate 360 degrees and tilt by up to 90 degrees, allowing light to be aimed with precision.

Vector Magnetic 40 is available in a choice of narrow, medium and wide beam angles and in colour temperatures of 2700K, 3000K, 4000K and 5000K. This makes it suitable for accenting merchandise, artwork or architectural elements, as well as contributing to more general ambient lighting when wider beams are used. Integrated LED sources with CRI 90 provide consistent, high quality illumination across the installation.

The fitting is offered in black, white and brushed metallic finishes to match the A.24 track profiles and other products within the Vector family. A range of optical accessories, including soft filters, dowsers and elliptical lenses, can be added to refine the beam for more demanding display or exhibition work. DALI dimming as standard allows the Vector Magnetic 40 to be integrated into coordinated lighting control schemes where scenes, levels and time schedules need to be managed centrally.

As the official UK distributor, we can support you with layouts, accessories and drivers. Contact us at artemide@davidvillagelighting.co.uk.

PRODUCT SPECIFICATION

Light Source:	Available in 2700K, 3000K, 4000K, 5000K or 6500K colour temperature. Wattage and lumen output vary by luminaire type.
IP Code:	20
Dimming:	Dimmable via Dali dimming systems. Please consult your electrician, additional wiring may be required on site.
Dimensions:	Multiple options are available, contact us for more information.



For all sales and technical enquiries, please contact:

+44 (0)114 263 4266

info@davidvillagelighting.co.uk

www.davidvillagelighting.co.uk